



FOR ANY DUTY

F



F PJ125E






FOTO. SROB



The outreaches stated are with a boom angle of 20° and are therefore not the maximum.

| PK 72002 Performance | | |
|---|-------------------|---------------|
| Technical Specifications (EN 12999 H1-B3) | | |
| Max. lifting moment | 68.0 mt/667.1 kNm | 491850 ft.lbs |
| Max. lifting capacity | 22000 kg/215.8 kN | 48500 lbs |
| Max. hydraulic outreach | 20.5 m | 67' 3" |
| Max. outreach (with fly-jib) | 31.9 m | 104' 8" |
| Slewing angle | endless | |
| Slewing torque | | |
| with 1 gear | 4.5 mt/44.1 kNm | 32510 ft.lbs |
| with 2 gears | 7.0 mt/68.7 kNm | 50650 ft.lbs |

| PK 72002 Performance | | |
|----------------------------|----------------------|------------------------------------|
| Standard crane | | |
| Outreach | 7.7 m | 25' 3" |
| Stabilizer spread standard | 8.6 m | 28' 3" |
| Fitting space required | min. 1.50 m / 4' 11" | max. 1.65 m / 5' 5" |
| Width folded | 2.5 m | 8' 3" |
| Max. operating pressure | 330 bar | 4785 psi |
| Recommended pump capacity | from 80 l/min | 17.6 imp.gal./min 21.1 US gal./min |
| with RC- and LS-system | to 100 l/min | 22.0 imp.gal./min 26.4 US gal./min |
| Dead weight standard crane | 5750 kg | 12680 lbs |

Applications shown in the leaflet do not always correspond to the standard specifications. Design and specification are subject to change without prior notice.






72002-1

PALFINGER

Country-specific regulations must be considered for the crane installation.

www.palfinger.com



KP-PK72002M2+E, 03/05



2

RANGE OF EQUIPMENT

E



E PJ170E

